Ingersoll Rand。 **COMPRESSOR DATA SHEET** In Accordance with Federal Uniform Test Method for Certain Lubricated Air Compressors **Rotary Compressor: Fixed Speed** MODEL DATA - FOR COMPRESSED AIR 1 Manufacturer: Ingersoll Rand UP6 10-125 Model Number 8/17/2020 Date: 2 Water-cooled х Air-cooled Screw Type: 1 # of Stages: Rated Capacity at Full Load Operating Pressure a, e 36.1 acfm<sup>a, e</sup> 3\* Full Load Operating Pressure <sup>b</sup> 125 4\* psig<sup>b</sup> 5 Maximum Full Flow Operating Pressure <sup>c</sup> 125 psig<sup>c</sup> 10 6 Drive Motor Nameplate Rating hp 89.5 7 Drive Motor Nameplate Nominal Efficiency percent 8 Fan Motor Nameplate Rating (if applicable) na hp 9 Fan Motor Nameplate Nominal Efficiency percent na 10\* Total Package Input Power at Zero Flow<sup>e</sup> 6.1 kW<sup>e</sup> Total Package Input Power at Rated Capacity and Full  $kW^{d} \\$ 9.3 11 Load Operating Pressure<sup>d</sup>

\* For models that are tested in the CAGI Performance Verification Program, these are the items verified by the third party program administrator

Consult CAGI website for a list of participants in the third party verification program: www.cagi.org

Specific Package Input Power at Rated Capacity and Full

Load Operating Pressure<sup>e</sup>

Isentropic Efficiency

- NOTES: a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions.
  - b. The operating pressure at which the Capacity (item 3) and Electrical Consumption (item 11) were measured for this data sheet.
  - c. Maximum pressure attainable at full flow, usually the unload pressure setting for load/no load control or the maximum pressure attainable before capacity control begins. May require additional power.
  - d. Total package input power at other than reported operating points will vary with control strategy.
  - e. Tolerance is specified in ISO 1217, Annex C, as shown in table below.

NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

	Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power
Member	$\underline{m^3}/\underline{min}$	ft3 / min	%	%	%
	Below 0.5	Below 17.6	+/- 7	+/- 8	
	0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%
ROT 030.1	1.5 to 15	53 to 529.7	+/- 5	+/- 6	
	Above 15	Above 529.7	+/- 4	+/- 5	
12/19 Rev 3 This form was developed by the Compressed Air and Gas Institute for the use of its members participating in the PVP. CAGI has not independently verified the reported data.					

ECO 1406715 24517765 Rev C

25.6

58.6

 $kW/100 cfm^{e}$ 

Percent

12\*

13