

## COMPRESSOR DATA SHEET

## In Accordance with Federal Uniform Test Method for Certain Lubricated Air Compressors Rotary Compressor: Variable Frequency Drive

		essor: Variable Frequency Dr TA - FOR COMPRESSED AL			
1	Manufacturer: Ingersoll Rand				
	Model Number R110N-W145		Date:	4/28/2020	
2	Air-cooled X Water-cooled		Type:	Screw	
			# of Stages:	1	
3*	Full Load Operating Pressure b	100		psig <sup>b</sup>	
4	Drive Motor Nominal Rating	150		hp	
5	Drive Motor Nominal Efficiency	95.4		percent	
6	Fan Motor Nominal Rating (if applicable)	1.1		hp	
7	Fan Motor Nominal Efficiency	86.6		percent	
	Input Power (kW)	Capacity (acfm) a,d		Specific Power (kW/100 acfm) <sup>d</sup>	
	134.7	772.0	17.45	17.45	
	121.0	694.6	17.42		
8*	107.8	621.3	17.35		
	93.7	539.3	17.37		
	80.4	457.3	17.58		
Ì	68.0	377.4	377.4 18.02		
	56.0	299.0	18.73	18.73	
9*	Total Package Input Power at Zero Flow <sup>c, d</sup>	0.0		kW	
10	Isentropic Efficiency	0.8		percent	
11	35 30 30 25 400,100,100 200 300 400 500 600 700 800  Capacity (ACFM)				
	Note: Y-axis scale 1	only a visual representation of the data in 0 to 35, +5kW/100acfm increments if neces is Scale, 0 to 25% over maximum capacity			

<sup>\*</sup> For models that are tested in the CAGI Performance Verification Program, these are the items verified by the third party program administrator

Consult CAGI website for a list of participants in the third party verificatio <a href="www.cagi.org">www.cagi.org</a>

- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity (item 8) and Electrical Consumption (item 8) were measured for this data sheet.
- c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- d Tolerance is specified in ISO 1217, Annex C, as shown in table below.

NOTE: The terms "power" and "energy" are synonymous for purposes of this document

	Volume Flow Rate at specified conditions	Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power
$\underline{\text{m}}^3 / \underline{\text{min}}$	ft3 / min	%	%	%
Below 0.5	Below 17.6	+/- 7	+/- 8	
0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%
1.5 to 15	53 to 529.7	+/- 5	+/- 6	
Above 15	Above 529.7	+/- 4	+/- 5	

Member

ROT 031.1

12/19 Rev 3 This form was developed by the Compressed Air and Gas Institute for the use of its members participating in the PVP. CAGI has not independently verified the reported dat