

## **COMPRESSOR DATA SHEET**

## Federal Uniform Test Method for Certain Air Compressors Not Applicable

**Rotary Compressor: Variable Frequency Drive** 

	MODEL DATA - FO	OR COMPRESSED	AIR				
1	Manufacturer: Ingersoll Rand						
2	Model Number IRN125H-OF		Date:	Date: 02/20/20			
	Air-cooled X Water-cooled	Type: # of Stages:		Screw			
	Lubricated X Oil-Free			2			
3*	Full Load Operating Pressure <sup>b</sup>	100	psig <sup>b</sup>				
4	Drive Motor Nominal Rating	125	hp				
5	Drive Motor Nominal Efficiency	95.4	percent				
6	Fan Motor Nominal Rating (if applicable)	1	hp				
7	Fan Motor Nominal Efficiency	82.5	percent				
	Input Power (kW)	Capacity (acfm) a,d	Specific Power (kW/100 acfm) <sup>d</sup>				
	117.5	592	19.86				
	110.8	559	19.83				
8*	104.3	525	19.88				
	97.8	490	19.96				
	91.6	455	20.14				
	84.2	415	20.29				
9*	Total Package Input Power at Zero Flow <sup>c, d</sup>	0.0		kW			
10	35.00 30.00 \$\frac{\hat{Q}}{25.00}\$						
	Spedic Power 25.00						
	10.00 100 200	300 400 500	600 70	00 800			
	Capacity (ACFM)						

\*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator Consult CAGI website for a list of participants in the third party verification program: <a href="www.cagi.org">www.cagi.org</a>



- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E;
   ACFM is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.
- c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:

  NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Member

Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power	
m <sup>3</sup> /min	ft <sup>3</sup> / min	%	%	%	
Below 0.5	Below 17.6	+/- 7	+/- 8		
0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%	
1.5 to 15	53 to 529.7	+/- 5	+/- 6		
Above 15	Above 529.7	+/- 4	+/- 5		