

In Accordance with Federal Uniform Test Method for Certain Lubricated Air Compressors **Rotary Compressor: Fixed Speed**

MODEL DATA - FOR COMPRESSED AIR							
1	Manufacturer: Ingersoll Rand						
	Model Number: RS132ie-W110	Date:	3/20/2020				
2	Air-cooled X Water-cooled	Type:	Screw				
		# of Stages:	2				
3*	Rated Capacity at Full Load Operating Pressure a, e	975	acfm ^{a, e}				
4*	Full Load Operating Pressure ^b	100	psig ^b				
5	Maximum Full Flow Operating Pressure ^c	110	psig ^c				
6	Drive Motor Nominal Rating	175	hp				
7	Drive Motor Nominal Efficiency	96.0%	percent				
8	Fan Motor Nominal Rating (if applicable)	1.0	hp				
9	Fan Motor Nominal Efficiency	82.5%	percent				
10*	Total Package Input Power at Zero Flow ^e	55.1	kW ^e				
11	Total Package Input Power at Rated Capacity and Full Load Operating Pressure ^d	150.7	kW ^d				
12*	Package Specific Power at Rated Capacity and Full Load Operating Pressure ^e	15.5	kW/100 cfm ^e				
13	Isentropic Efficiency	86.0	Percent				

^{*} For models that are tested in the CAGI Performance Verification Program, these are the items verified by the third party program administrator Consult CAGI website for a list of participants in the third party verification program:

- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity (item 3) and Electrical Consumption (item 11) were measured for this data sheet.
- c. Maximum pressure attainable at full flow, usually the unload pressure setting for load/no load control or the maximum pressure attainable before capacity control begins. May require additional power.
- d. Total package input power at other than reported operating points will vary with control strategy.
- e. Tolerance is specified in ISO 1217, Annex C, as shown in table below.

NOTE: The terms "power" and "energy" are synonymous for purposes of this document.



12/19 Rev 3

ROT 030.1

	Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power		
Member	$\underline{m}^3 / \underline{min}$	<u>ft³ / min</u>	%	%	%		
	Below 0.5	Below 17.6	+/- 7	+/- 8			
	0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%		
	1.5 to 15	53 to 529.7	+/- 5	+/- 6			
	Above 15	Above 529.7	+/- 4	+/- 5			
This form was developed by the Compressed Air and Gas Institute for the use of its members participating in the PVP. CAGI has not independently verified the reported data.							

Rev B

47659956001

ECO 1341195