

## COMPRESSOR DATA SHEET

## In Accordance with Federal Uniform Test Method for Certain Lubricated Air Compressors Rotary Compressor: Variable Frequency Drive

		- FOR COMPRESSED AIR			
1	Manufacturer: Ingersoll Rand				
	Model Number: RS15n-A145		Date:	4/13/2020	
2	X Air-cooled Water-cooled		Type:	Screw	
		#	of Stages:	1	
3*	Full Load Operating Pressure <sup>b</sup>	135		psig <sup>b</sup>	
4	Drive Motor Nominal Rating	20		hp	
5	Drive Motor Nominal Efficiency	92.1		percent	
6	Fan Motor Nominal Rating (if applicable)	0.7		hp	
7	Fan Motor Nominal Efficiency	79.5		percent	
	Input Power (kW)	Capacity (acfm) a,d	Specific Power (kW/100 acfm) <sup>d</sup>		
	18.5	77.4	23.86		
	16.8	69.8	24.12		
8*	15.2	62.1	24.44		
	13.4	53.8	24.89		
	11.7	45.4	25.72		
	9.8	38.0 25.88		25.88	
9*	Total Package Input Power at Zero Flow <sup>c,d</sup>	0		kW	
10	Isentropic Efficiency	63.6	percent		
	35				
	30				
	<b>DAC</b> 25				
11	(kw/100AcFM) 25 20 CM 20				
	15				
	10 10 20 30	40 50 60 Capacity (ACFM)	70	80 90	

<sup>\*</sup> For models that are tested in the CAGI Performance Verification Program, these are the items verified by the third party program administrator

NOTES:

Consult CAGI website for a list of participants in the third party verification program: www.cagi.org a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at

- b. The operating pressure at which the Capacity (item 8) and Electrical Consumption (item 8) were measured
- for this data sheet.
  c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- d Tolerance is specified in ISO 1217, Annex C, as shown in table below.

NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Member

ROT 031.1

Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power
at specified conditions		volume Flow Rate	Consumption	1-low Fower
m <sup>3</sup> /min	ft3 / min	%	%	%
Below 0.5	Below 17.6	+/- 7	+/- 8	
0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%
1.5 to 15	53 to 529.7	+/- 5	+/- 6	
Above 15	Above 529.7	+/- 4	+/- 5	

This form was developed by the Compressed Air and Gas Institute for the use of its members participating in the PVP. CAGI has not independently verified the reported data