

## COMPRESSOR DATA SHEET

In Accordance with Federal Uniform Test Method for Certain Lubricated Air Compressors

		÷	Compressor: Var EL DATA - FOR	-	Į.		
1	Manufacturer: Ingerso		EL DATA - FOK	COMP RESS	DED AIK		
	Model Number:	RS45n-W145			Date	: 2/19/2021	
2	Air-cooled X Water-cooled				Туре		
					# of Stages	: 1	
3*	Full Load Operating Pr	essure <sup>b</sup>			115	psig <sup>b</sup>	
4	Drive Motor Nominal Rating				60	hp	
5	Drive Motor Nominal Efficiency				95.4	percent	
6	Fan Motor Nominal Rating (if applicable)				0.4	hp	
7	Fan Motor Nominal Efficiency				87.5	percent	
	Input Power (kW)				Capacity (acfm) <sup>a,d</sup>	Specific Power (kW/100 acfm) <sup>d</sup>	
Ī	51.7				282.1	18.95	
Ī	47.1				257.5	18.90	
8*	42.5				232.4	18.89	
Ī	37.8				206.2	18.93	
Ī	33.1				179.7	19.05	
Ī	15.2				72.5	21.72	
9*	Total Package Input Power at Zero Flow <sup>c,d</sup>				0	kW	
10	Isentropic Efficiency				77.1	percent	
11	35 30 25 02 25 02 25 02 20 20						
			e: Graph is only a visual -axis scale 10 to 35, +5kV		ts if necessary above 35	250 30	

\* For models that are tested in the CAGI Performance Verification Program, these are the items verified by the third party program administrator

Consult CAGI website for a list of participants in the third party verification program:

NOTES: a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions.



b. The operating pressure at which the Capacity (item 8) and Electrical Consumption (item 8) were measured for this data sheet.

c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.

d Tolerance is specified in ISO 1217, Annex C, as shown in table below. NOTE: The terms "power" and "energy" are synonymous for purposes of this docur

Member		Volume Flow Rate specified conditions	Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power
	$\underline{m^3}/\underline{min}$	ft3 / min	%	%	%
	Below 0.5	Below 17.6	+/- 7	+/- 8	
	0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%
ROT 030.1	1.5 to 15	53 to 529.7	+/- 5	+/- 6	
	Above 15	Above 529.7	+/- 4	+/- 5	

Rev B

www.cagi.org