DRYER DATA SHEET Refrigerant Dryers

| MODEL DATA | | | | | | |
|------------|-------------------------------------|---------------------------|-------------|-------------------|--|--|
| 1 | Manufacturer | Ingersoll Rand Industrial | | | | |
| 2 | Date | July 10, 2024 | | | | |
| 3 | Model Number | DAV510INA400 | | | | |
| 4 | Cycling/Non-Cycling | Non-Cycling | | | | |
| 5 | Refrigerant Type | R407C | | | | |
| 6 | Air/Water Cooled | Air | | | | |
| 7 | Voltage | 460/3/60 | | | | |
| | DESCRIPTION | FULL FLOW | 10% FLOW | UNITS | | |
| 8 | Tested Flow ^a | 300 | 30 | scfm ^b | | |
| 9 | Outlet Pressure Dew Point | 43.7 | 33.4 | °F | | |
| 10 | Pressure Drop | 1.64 | 0.06 | psi(d) | | |
| 11 | Total Dryer Input Power | 2.32 | 2.09 | kW | | |
| 12 | Specific Package Power ^c | 0.77 | 6.97 | kW/100 scfm | | |

Notes:

a. Dryer ratings at the following inlet conditions to the dryer (as per adopted CAGI Standard ADF 100):

| • | Inlet Compressed Air Temperature: | 100°F (37.78°C) |
|---|--|--------------------|
| • | Inlet Compressed Air Pressure: | 100 psig (6.9 Bar) |
| • | Max. Ambient Air Temperature: | 100°F (37.78°C) |
| • | Inlet Compressed Air Relative Humidity | 100% (Saturated) |

- b. SCFM defined as the volume of free air in cubic feet per minute measured at 14.5 psia (1.0 Bar), 68°F (20°C) temperature and 0% R.H. (0 WVP).
- c. (Total Dryer Input Power/tested flow) x 100

Member



This form was developed by the Compressed Air and Gas Institute for the use of its members. CAGI has not independently verified the reported data.