

Next Generation R-Series Oil-Flooded Rotary Screw Air Compressors

200-250 kW (250-350 hp)



Ingersoll Rand works to keep you ahead of your competition with Next Generation R-Series air compressors that boost productivity, lower operating expenses and extend equipment life.

Next Generation R-Series air compressors. The intelligence you need—to win.

World-class performance

- **State-of-the-art airend** delivers as much as 10% improved efficiency and 16% greater airflow capacity; two stage airend available for even greater efficiency and reduced bearing load to extend life
- **PAC™ protection, V-Shield™ technology and free-floating cooling system** help maximise uptime
- **Xe-Series controller with intuitive, high-resolution colour display** offers remote access with any common, current web browser
- **IE3 Premium Efficiency motor** delivers significant energy savings, and the optional variable speed drive (VSD) further decreases energy demands
- **Air-cooled and water-cooled options** to best match your operating environment
- **Harsh environment options** for high and low ambient temperature as well as outdoor operation

Standard Features include:	Optional Features include:
Premium IP55 motor with space heater and RTD	Outdoor modification/rain protection
Star-delta reduced voltage starter	Low ambient temperature protection to -10°C
Noise attenuation enclosure with hinged, removable doors for easy service access	High ambient rating up to 55°C
Stainless steel and PTFE coolant hoses with repeatable leak free connections	Premium high dust filtration
Free-floating cooling system optimised for efficiency and serviceability	Fluid containment system
PAC™ Protection adjusts operating parameters in response to compressor operation	Ultra FG lubricant
Package rating for operation up to 46°C	Automatic power outage restart option (PORO)
Package pre-filter	Soft-start reduced voltage starter
Control panel with enhanced environmental protection against dust and liquids	Flow control modulation control
Long-life consumables and 16,000-hour life Ultra EL lubricant	Phase monitor protection

i Ingersoll Rand – 50 Hz Performance					
Model	Max. Pressure bar	Nominal Power kW	Capacity (FAD)* m ³ /min	Dimensions (Length x Width x Height) mm	Weight kg
200i	7.5	200	41.5	3752 x 2150 x 2502	6275
	8.5		40.0		
	10.0		35.7		
250i	7.5	250	50.2	3752 x 2150 x 2502	6275
	8.5		48.1		
	10.0		43.0		

ie Ingersoll Rand – 50 Hz Performance					
200ie	7.5	200	43.6	4320 x 2150 x 2502	8336
	8.5		41.0		
	10.0		38.5		
	14.0		31.0		
250ie	7.5	250	54.1	4320 x 2150 x 2502	8336
	8.5		50.8		
	10.0		46.6		
	14.0		38.8		

n Ingersoll Rand – 50 Hz Performance					
200n	7.0-10.0	200	16.8-41.2	3752 x 2150 x 2502	6275
250n		250	16.8-49.2		

ne Ingersoll Rand – 50 Hz Performance					
200ne	7.0-10.0	200	18.6-43.4	4320 x 2150 x 2502	8336
250ne		250	18.6-53.1		

*FAD (Free Air Delivery) is full package performance including all losses, tested per ISO 1217:2009 Annex C



IngersollRandProducts.com

Ingersoll Rand (NYSE:IR) advances the quality of life by creating comfortable, sustainable and efficient environments. Our people and our family of brands—including Club Car®, Ingersoll Rand®, Thermo King® and Trane®—work together to enhance the quality and comfort of air in homes and buildings; transport and protect food and perishables; and increase industrial productivity and efficiency. We are a \$13 billion global business committed to a world of sustainable progress and enduring results.



Ingersoll Rand, IR, the IR logo, PAC software and V-Shield are trademarks of Ingersoll Rand, its subsidiaries and/or affiliates. All other trademarks are the property of their respective owners. Ingersoll Rand compressors are not designed, intended or approved for breathing air applications. Ingersoll Rand does not approve specialized equipment for breathing air applications and assumes no responsibility or liability for compressors used for breathing air service. Nothing contained on these pages is intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale of products shall be in accordance with Ingersoll Rand's standard terms and conditions of sale for such products, which are available upon request. Product improvement is a continuing goal at Ingersoll Rand. Any designs, diagrams, pictures, photographs and specifications contained within this document are for representative purposes only and may include optional scope and/or functionality and are subject to change without notice or obligation.

We are committed to using environmentally conscious print practices

© 2017 Ingersoll Rand ENG52768