

GHH RAND®


CF128LG – Oil-Injected Screw Compressor Airend

The CF128LG is a single stage oil-injected screw compressor airend with an integrated gear drive, which can be used for general industrial applications.

Operating Range

Parameters	Units	Min	Max
Power	kW / hp	27 / 36.2	222.4/298.3
Discharge Pressure, abs.	bar / psi	6 / 87	11.5 / 167
Volume Flow	m ³ /min / cfm	5.6 / 198.2	29 / 1024

Medium: Air, Inlet temp. 20°C/68°F, Discharge temp. 80°C/176°F, Inlet pressure 1 bar(a)/14.5 psi(a), RH: 60%



Technical Data

Parameters	Units	Data
Length	mm	909
Width	mm	433
Height	mm	370
Weight	kg	330
Inlet DN	mm	150
Outlet DN	mm	125

GHH RAND recommends:



- Maximize life and efficiency with Primecool or Primecool Plus (food grade)
- Ask your sales rep. for details

GHH RAND Schraubenkompressoren GmbH
Max-Planck-Ring 27 • 46049 Oberhausen • Germany
Phone +49 (0) 208 9994-0 • Fax +49 (0) 208 9994-111
industrial-sales@ghhrand.com • www.ghhrand.com